



Revision Date: 5/10/17

Page 1 of 5

1

PRODUCT AND COMPANY IDENTIFICATION

Manufacturer

Natural Sand Company, Inc. 4783 HARLANSBURG ROAD SLIPPERY ROCK, PA 16057

Emergency: Emergency Phone: (724) 530-2298

Contact: Natural Sand Company

 Phone:
 (866) 867-4250

 Fax:
 (724) 264-4174

 Email:
 safety@duraedge.com

 Web:
 www.duraedge.com

Product Name: DuraEdge® Premium Clay

Revision Date: 5/10/17 **Common Name:** Clay

Description: Natural occuring clay mineral Product Use: Baseball & Softball Infields



Revision Date: 5/10/17

Page 2 of 5

2

HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Health, Specific target organ toxicity - Single exposure, 3

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: WARNING GHS Hazard Pictograms:



GHS Hazard Statements:

H335 - May cause respiratory irritation

GHS Precautionary Statements:

P201 - Obtain special instructions before use.

P202 - Do not handle until all safety precautions have been read and understood.

P261 - Avoid breathing dust.

Hazards not Otherwise Classified (HNOC) or not Covered by GHS

Inhalation: Lungs

Skin Contact: Wash with soap and water until clean

Eye Contact: Wash out with water

NFPA: Health = 1, Fire = 0, Reactivity = 0, Specific Hazard = n/a



3

COMPOSITION/INFORMATION OF INGREDIENTS

Ingredients:

Cas# % Chemical Name

14808607 <1% Crystalline Silica, Quartz



Revision Date: 5/10/17

Page 3 of 5

4 **FIRST AID MEASURES**

Inhalation: Move to fresh air.

Skin Contact: Wash throughly with soap and water.

Eye Contact: Flush thoroughly with water. See a physician if discomfort persists. Ingestion: None. If large quantities are ingested consult your physician.

5 FIRE FIGHTING MEASURES

Non-flammable and non-hazardous

6 **ACCIDENTAL RELEASE MEASURES**

Steps to be taken in case material is released or spilled: If uncontaminated, sweep up or collect, and reuse as product. If contaminated with other materials, collect in suitable containers.

7 HANDLING AND STORAGE

Follow the personal protection and controls identified in section 8 of the SDS when handling this **Handling Precautions:**

product.

Keep indoors or cover with a tarp to keep dust levels down. **Storage Requirements:**

8 **EXPOSURE CONTROLS/PERSONAL PROTECTION**

Personal Protective Respiratory Protection: If dust concentrations exceed recommended Permissible Exposure Limits, use **Equipment:**

NIOSH- approved dust respirators, with approval TC-21C-xxx, until feasible engineering controls are

completed.

Ventilation: Local exhaust or other ventilation that will reduce dust concentrations to less than

Permissible Exposure Limits is recommended.

Eye Protection: If high dust concentrations exist, tight-fitting goggles are recommended to reduce dust

exposure to the eyes.

Other Protective Equipment: Optional.

Exposure Limits (respirable fraction) in Air: OSHA & MSHA - PEL

ACGIH - TLV

10mg/m3 % SiO2 + 2 (8-Hour TWA)

0.05 mg/cubic meter (8-Hour TWA)

NIOSH 0.05mg/cubic meter (10-Hour TWA, 40-hour work week)

Exposure Limits refer to the respirable fraction.


PEL means OSHA Permissible Exposure Limit.

TLV means American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Value.

MSHA means Mine Safety and Health Administration Exposure Limit.

TWA means 8 hour Time Weighted Average.

GHS Safety Data Sheet





DuraEdge® Premium Clay

Revision Date: 5/10/17

Page 4 of 5

9 PHYSICAL AND CHEMICAL PROPERTIES

Red-Brown clay particles Appearance:

1.6 approx. 100 P.C.F at 12 % moisture Spec Grav./Density: **Bulk Density:**

10 STABILITY AND REACTIVITY

Chemical Stability: DuraEdge Premium Clay is stable under all normal conditions.

Conditions to Avoid: None None Materials to Avoid: None Known **Hazardous Decomposition:** Will not occur. **Hazardous Polymerization:**

11 **TOXICOLOGICAL INFORMATION**

Inhalation- N.E.

Intravenous- Rat - LD50:15mg/kg Oral - Rat - LD50:3160 mg/kg

12 **ECOLOGICAL INFORMATION**

Naturally occuring, inorganic, crystalline, absorbent, clay minerals, such as Attapulgalite and Montmorillonite, are used in a wide variety of commercial, industrial, and consumer applications.

13 **DISPOSAL CONSIDERATIONS**

Can be disposed of in an approved disposal facility, in accordance with applicable federal, state, and local regulations. The nature and extent of contamination, if any, may require use of specialized disposal methods.

14 TRANSPORT INFORMATION

Ground Clay contains crystalline silica in solid form

WHMIS Classification D2A

WHMIS Label on each package

Not TDG regulated





Revision Date: 5/10/17

Page 5 of 5

15

REGULATORY INFORMATION

Component (CAS#) [%] - CODES

Silica, crystalline quartz (14808607) [<1%] MASS, NRC, OSHAWAC, PA, TSCA, TXAIR

Regulatory CODE Descriptions

MASS = MA Massachusetts Hazardous Substances List
NRC = Nationally Recognized Carcinogens
OSHAWAC = OSHA Workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
TSCA = Toxic Substances Control Act
TXAIR = TX Air Contaminants with Health Effects Screening Level

COMPONENT / (CAS/PERC) / CODES

*Silica, crystalline quartz (14808607 <1%) MASS, NRC, OSHAWAC, PA, TSCA, TXAIR

REGULATORY KEY DESCRIPTIONS

MASS = MA Massachusetts Hazardous Substances List
NRC = Nationally Recognized Carcinogens
OSHAWAC = OSHA Workplace Air Contaminants
PA = PA Right-To-Know List of Hazardous Substances
TXAIR = TX Air Contaminants with Health Effects Sc
reening Level

TSCA = Toxic Substances Control Act

16

OTHER INFORMATION

Disclaimer:

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).