

Indication of immediate medical attention and special treatment, if

necessary

## **SAFETY DATA SHEET**

			Page 1 of 4		
SECTION 1: PRODUCT	AND COMPA	ANY IDENTIFICATION			
PRODUCT IDENTIFIER	Pro Dry Infield Conditioner				
CHEMICAL NAME	Montmorillonite Clay, Calcined				
CHEMICAL FAMILY	Clay				
MATERIAL USE	Soil Amendment				
RESTRICTION ON USE	None Known				
MANUFACTURER	EP Minerals, LLC., 9785 Gateway Dr., Reno, NV 89521				
TELEPHONE NO.	(775) 824 7600 (Monday – Friday 8:00 am PST – 5:00 pm PST)				
EMERGENCY TELEPHONE NO.	(775) 824 7600 (M	onday – Friday 8:00 am PST – 5:00 pm PS	T)		
MANUFACTURED FOR:	Dura Edge Products, 149 South Broad Street, Grove City, PA 16127 Phone: 724-264-4174				
SDS DATE OF PREPARATION	January 1, 2019				
SECTION 2: HAZARDS	IDENTIFICAT	ΓΙΟΝ			
OSHA GHS HAZARD CLASSIFICATION	Carcinogen Category 1A Specific Target Organ Toxicity, Repeated Exposure Category 1				
HAZARDS NOT OTHERWISE CLASSIFIED	None				
LABEL ELEMENTS	DANGER May cause cancer by inhalation. Causes damage to lungs through prolonged or repeated exposure. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Do not breathe dust. Wear eye protection. If exposed or concerned: Get medical advice. Dispose of contents in accordance with local, state and federal regulations.				
SECTION 3: COMPOSIT	ION / INFOR	MATION ON INGREDIENTS	<u> </u>		
INGREDIENT IDENTIFICATION		APPROXIMATE CONCENTRATION (%)	C.A.S. NUMBERS		
Montmorillonite Clay, Calcined (contains 10-15% Crystalline Silica - Quartz)		100%	70892-59-0 14808-60-7		
SECTION 4: FIRST AID	MEASURES		1		
EYE	Flush eyes with ge	nerous quantities of water or eye rinse solu	tion. Consult physician if irritation persists.		
SKIN	Use moisture renewing lotions if dryness occurs.				
INGESTION	Drink generous amounts of water to reduce bulk and drying effects.				
INHALATION	Remove to fresh air. Blow nose to evacuate dust.				
Most important symptoms/effects, acute and delayed	Dust may cause abrasive irritation to eyes. Prolonged skin contact may cause dryness. Dust may cause nose, throat and upper respiratory tract irritation. Prolonged inhalation of respirable dust containing silica may cause a progressive lung disease, silicosis and lung cancer. See Section 11 for additional information.				

Immediate medical attention is not normally required. If dust irritates the eyes, seek medical attention.

	ı					
MATERIAL NAME	Pro Dry Infield Conditioner				Page 2 of 4	
SECTION 5: FIRE FIGHT	TING M	EASURES				
EXTINGUISHING MEDIA	Not applicable, the material is not combustible.					
SPECIFIC HAZARDS ARISING FROM THE CHEMICAL	Not appli	Not applicable, the material is not combustible.				
SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS	Not appli	Not applicable, the material is not combustible.				
<b>SECTION 6: ACCIDENT</b>	AL REI	EASE MEASUR	ES			
PERSONAL PRECAUTIONS	If dust is present, use respirator fitted with particulate filter as specified in Section 8. Protect eyes with goggles. Do not breathe dust.					
ENVIRONMENTAL PRECAUTIONS	This mate	This material is not a significant environmental concern.				
METHODS AND MATERIALS FOR CONTAINMENT AND CLEANING UP	Vacuum	Vacuum clean spillage or wet sweep. Avoid creating airborne dust. Place in a container for use or disposal.				
SECTION 7: HANDLING	AND S	TORAGE				
PRECAUTIONS FOR SAFE HANDLING	Minimize dust generation. Avoid contact with eyes. Do not breathe dust. Repair or dispose of broken bags. Observe all label precautions and warnings. Flammable or hazardous substances may retain such characteristics after absorption. Care should be taken to store and dispose of waste material in accordance with instructions of manufacturer of substance absorbed and applicable laws. Do not use with hydrofluoric acid or concentrated caustic solutions.					
CONDITIONS FOR SAFE STORAGE	Store in a dry place to maintain packaging integrity and product quality. Store product separately from feed, food, pesticides and fertilizers so that cross contaminations does not occur. Do not store near hydrofluoric acid or concentrated caustic solutions.					
SECTION 8: EXPOSURE	CONT	ROLS / PERSON	NAL PROTEC	CTION		
EXPOSURE GUIDELINES:			•	ered by the OSHA Silica Standard (2	9CFR1910.1053) and	
Component		the OSHA PEL associate OSHA PEL	ACGIH TLV	MSHA PEL	NIOSH REL	
Montmorillonite Clay, Calcined (as Particulates not otherwise classified)		5 mg/m³ respirable dust 15 mg/m³ total dust	None Established	5 mg/m³ respirable dust 15 mg/m³ total dust	None Established	
Crystalline Silica (Quartz)						
		30 mg/m <sup>3</sup> % SiO <sub>2</sub> +2 total dust 10 mg/m <sup>3</sup> % SiO <sub>2</sub> +2 Respirable dust	0.025 mg/ m <sup>3</sup> Respirable dust	$\frac{30 \text{ mg/m}^3}{\% \text{ SiO}_2 + 2}$ $\text{total dust}$ $\frac{10 \text{ mg/m}^3}{\% \text{ SiO}_2 + 2}$ Respirable dust	0.05 mg/ m <sup>3</sup> Respirable dust	
ENGINEERING CONTROLS		total dust  10 mg/m³ % SiO <sub>2</sub> +2 Respirable dust eral or local exhaust ventila	Respirable dust	total dust  10 mg/m³ % SiO₂+2  Respirable dust  within recommended exposure limits	Respirable dust	
ENGINEERING CONTROLS PERSONAL PROTECTIVE EQUIPMENT:		total dust  10 mg/m³ % SiO <sub>2</sub> +2 Respirable dust eral or local exhaust ventila	Respirable dust	total dust 10 mg/m³ % SiO <sub>2</sub> +2 Respirable dust	Respirable dust	
PERSONAL PROTECTIVE	publication	total dust  10 mg/m³ % SiO <sub>2</sub> +2 Respirable dust eral or local exhaust ventila	Respirable dust	total dust  10 mg/m³ % SiO₂+2  Respirable dust  within recommended exposure limits	Respirable dust	
PERSONAL PROTECTIVE EQUIPMENT:	publication Goggles	total dust  10 mg/m³ % SiO₂+2 Respirable dust eral or local exhaust ventilation" of	Respirable dust	total dust  10 mg/m³ % SiO₂+2  Respirable dust  within recommended exposure limits	Respirable dust	
PERSONAL PROTECTIVE EQUIPMENT: EYE / FACE PROTECTION	Goggles  No speci  Respirate present. or half-m than ten filters is r PEL use greater the	total dust  10 mg/m³ % SiO₂+2 Respirable dust  eral or local exhaust ventilation "Industrial Ventilation" of the protect from dust  al equipment is needed.  ors fitted with filters certified in the dust concentration is east respirator with a N95 (10) times and less than filtercommended. If dust conca power air-purifying (positions)	Respirable dust  ation to control dust or similar publications  and to standard 42CFF s less than ten (10) t dust filter or a single fity (50) times the PE centration is greater itive pressure) respir es the PEL use a typ	total dust  10 mg/m³ % SiO₂+2  Respirable dust  within recommended exposure limits	Respirable dust  S. Refer to ACGIH  To when dust is t (PEL) use a quarter ncentration is greater with replaceable N95 dred (200) times the dust concentration is	

MATERIAL NAME	Pro Dry Infield Conditioner	Page 3 of 4			
SECTION 9: PHYSICAL	AND CHEMICAL PRO	PERTIES	·		
APPEARANCE, COLOR	Reddish Brown granules	ODOR	Odorless		
PHYSICAL STATE	Solid	ODOR THRESHOLD	Not applicable		
VAPOR PRESSURE	Not applicable	VAPOR DENSITY	Not applicable		
BOILING POINT	Not applicable	MELTING POINT	Unknown		
FLASH POINT	Not applicable	pH (10% SUSPENSION)	Unknown		
FLAMMABILITY LIMITS	Not applicable	EVAPORATION RATE	Not applicable		
DECOMPOSITION TEMPERATURE	Unknown	SPEC. GRAVITY / RELATIVE DENSITY	2.2		
AUTOIGNITION TEMPERATURE	Not applicable	PARTITION COEFFICIENT – n- OCTANOL/WATER	Not applicable		
FLAMMABILITY (solid/gas)	Not applicable	SOLUBILITY – WATER	< 2%		
		VISCOSITY	Not applicable		
SECTION 10: STABILIT	Y AND REACTIVITY				
REACTIVITY	Material is not reactive.				
CHEMICAL STABILITY	Material is stable.				
POSSIBILITY OF HAZARDOUS REACTIONS	Material is not reactive under normal conditions of handling unless mixed with incompatible substances below.				
CONDITIONS TO AVOID	Not applicable				
INCOMPATIBLE MATERIALS	Unsaturated organic compounds, such as turpentine and vegetable oil, hydrofluoric acid and concentrated caustic solutions may react violently with the product.				
HAZARDOUS DECOMPOSITION PRODUCTS	Not applicable				
SECTION 11: TOXICOL	OGICAL INFORMATIO	N			
POTENTIAL HEALTH EFFECTS					
Likely Routes of Exposure	See below				
EYE	May cause irritation (tear formation and redness) if dust gets in eyes.				
SKIN	Not absorbed by the skin, but may cause dryness if prolonged exposure.				
INGESTION	Ingestion of small quantities is not considered harmful, but may cause irritation of the mouth, throat and stomach.				
INHALATION	Acute inhalation can cause dryness of the nasal passage and lung congestion, coughing and general throat irritation. Acute inhalation of high concentrations of respirable crystalline silica may cause acute silicosis.				
CHRONIC EFFECTS	This product contains naturally occurring crystalline silica. Respirable crystalline silica may cause lung cancer and lung disease (silicosis) if inhaled for prolonged periods. Symptoms of silicosis include wheezing, cough and shortness of breath.				
CARCINOGENICITY	This natural product is composed predominantly of clay, but contains some crystalline silica. Respirable crystalline silica (quartz) is classified by IARC and NTP as a known human carcinogen. Crystalline silica is only known to cause cancer when inhaled in a respirable form. It is not known to cause cancer by any other route of exposure.				
NTP	Respirable crystalline silica (qua	rtz) is classified as a known human carci	nogen.		
IARC	Respirable crystalline silica (qua	rtz) is classified as a known human carci	nogen.		
NUMERICAL MEASURES OF TOXICITY	No data available				

	1					
MATERIAL NAME	Pro I	Dry Infield Conditioner Page 4 of 4				
CORROSIVENESS, SENSITIZATION, IRRITANCY		Not applicable				
REPRODUCTIVE TOXICITY		Not available				
TERATOGENICITY, MUTAGENICITY		Not available				
SECTION 12: ECOL	OGI	CAL INFORMATION				
ECOTOXICITY:		No toxicity is expected				
PERSISTENCE AND DEGRADABILITY		Non-biodegradable, inert.				
BIOACCUMULATIVE POTENT	TAL	Little potential for bioaccumulation				
MOBILITY IN SOIL		No mobility				
OTHER ADVERSE EFFECTS		None known				
SECTION 13: DISPO	SAL	CONSIDERATIONS				
WASTE DISPOSAL		this material as supplied becomes a waste, use solid waste disposal common to landfill type operations or in slurry to imps. Not considered a hazardous waste under RCRA (40CFR Part 261).				
PACKAGING DISPOSAL		Dispose of in accordance with applicable laws and regulations, typically solid waste disposal common to landfill type operations.				
SECTION 14: TRANS	SPO	RT INFORMATION				
BASIC SHIPPING INFORMATION	DOT shipping classification 55 (no restrictions). Technical name is "Calcined Clay".					
ADDITIONAL INFORMATION	No special requirements or placarding necessary.					
SECTION 15: REGU	LAT	ORY INFORMATION				
U.S. FEDERAL:						
TSCA	Mont	Montmorillonite and Quartz appear on the EPA TSCA inventory list.				
CERCLA		Montmorillonite is not classified as a hazardous substance under regulations of the Comprehensive Environmental Response Compensation and Liability Act (CERCLA), 40 CFR 302.				
SARA TITLE III	Not I	Not listed.				
California Proposition 65:		/ARNING: This product can expose you to crystallin er. For more information go to www.P65Warnings.co		, which is known to the State of C	California to cause	
SECTION 16: OTHE	R IN	FORMATION				
		A Extreme	HMIS	0* Health		
		4-Extreme 3-High 0 0 2-Moderate 1-Slight 0-Insignificant		0 Flammability		
				0 Reactivity		
		V magnitudit		E Protective Equipment		
ORIGINAL ISSUE DATE	January 1, 2019					
REVISION DATE	January 1, 2019					
REVISION NO.	1					
	<u> </u>					

**Disclaimer:** As of the date of the preparation of this document, the foregoing information is believed to be accurate and is provided in good faith to comply with applicable federal and state laws. No warranty, representation or guaranty of any kind, express or implied, is hereby provided or intended with respect to the completeness of the information contained herein. We accept no responsibility and disclaim all liability for any harmful effects which may be caused by the purchase, resale, use or exposure to our product. Customer users of silica must comply with all applicable health and safety laws, regulations and orders, including OSHA Hazardous Communication Standard.